

# HLB 700

## Safety post

EN 795/A, CEN/TS 16415



### SPECIAL FEATURES



Protection for max. 3 users

**INOX**

Made of stainless steel

### PARAMETERS

|                                    |                 |
|------------------------------------|-----------------|
| Material                           | stainless steel |
| Static strength                    | 14 kN           |
| Bore diameter of the catch point Ø | 45 mm           |
| Max. number of users               | 3               |

|          |                 |
|----------|-----------------|
| Material | stainless steel |
|----------|-----------------|

### MOUNTING KIT

|          |        |
|----------|--------|
| Quantity | 1 pcs. |
|----------|--------|

### POST

|                 |        |
|-----------------|--------|
| Height variants | 500 mm |
|-----------------|--------|

### VARIANTS

| ref. no. | version                                 | mounting type        |
|----------|-----------------------------------------|----------------------|
| HLB700   | anchorage point + concrete assembly kit | Chemiczna HVU2 HILTI |

**PROTEKT**

PROTEKT Grzegorz Laszkiewicz Spolka z o.o. Starorudzka 9, 93-403 Lodz, POLAND  
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

WWW.PROTEKT.PL

EXPORT SALES DEPARTMENT Skromna 6, 93-405 Lodz, POLAND  
Phone: +48 42 29 29 500, export@protekt.com.pl, Fax +48 42 680-20-93

# HLB 700

Safety post

## ADDITIONAL PHOTOS

---

