

# DATASHEET

## MILAN 2.0



### GENERAL

Art.Nr:	A-027
GTIN:	4030281155843
E-class number:	40-21-01-01
Customs tariff number:	84798997

Standards:	ANSI Z359.9-2021, EN 341:2011/1A, MEETS CSA Z259.2.3:16/1/B
Net weight:	2.29 kg
Gross weight:	2.29 kg

# DATASHEET

## MILAN 2.0

MILAN is THE industrial standard evacuation device worldwide. The centrifugally controlled brake maintains a constant descent speed of 0.9 m/s, thus ensuring fast and safe evacuation. The ultra-robust housing made in Germany is CNC-milled from a solid block aluminium. - suitable for 2-person use and for alternating abseiling - abseiling heights up to 500 m - rescue operations of any kind at any place With special [SEAL PACs](<https://bit.ly/3408bTx>) an extended lifetime of up to 15 years can be guaranteed, which can even be doubled once within a resealing process to 30 years. Note: When working at heights, a suitable rescue concept based on a risk assessment is essential. MILAN offers a variety of applications for different rescue scenarios. To master these techniques, the user must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

### FEATURES

Colour:	Black, Orange, White
Lifting function:	No
Max. abseiling height:	500 m
Max. load 1 person:	141.00 kg
Max. load 2 persons:	280.00 kg
Maximum lifetime:	20 years
Max. number of persons:	2
Maximum load:	280.00 kg
Minimum compatible rope diameter:	9.00 mm
Maximum compatible rope diameter:	9.00 mm
Max. Abseil speed:	0.90 m/s
Min. temperature:	-35 °C
Max. temperature:	60 °C
Panic function:	No
Rescue function:	Yes

### MATERIAL

Material:	Aluminium, Steel, Polyamide
-----------	-----------------------------