

EN 795, CEN/TS 16415



The lightweight aluminum safety tripod TM9-N is an anchor point compliant with the EN795/B and TS 16415/B norms and can be used as a component of fall protection equipment. The TM9-N tripod provides protection for up to 3 people simultaneously. The TM9-N tripod consists of a powder-coated steel head, equipped with 3 ball-bearing polyamide rollers for guiding the work rope of RUP and CRW series devices. The head is also equipped with 3 anchor points located on the sides of the head. Each of these points can be used as an anchor point for fall protection equipment. One such point can only be used by 1 user at a time.

SPECIAL FEATURES



Maximum load 500 kg



Protection for max. 3 users



Made of aluminium

PARAMETERS

Height	209 cm	Finishing	anodizing
Mounting hole diameter Ø	149 mm		
Leg spacing	128 mm		
Weight of tripod	15.45 kg		
Transport dimensions	1760 x 260 x 230 mm		
Max. number of users for lifting and lowering	3		
Max. weight of load to be lifted or lowered	500 kg		

LEGS

Material	aluminium
----------	-----------

FEET

Material	carbon fibre plastic
----------	----------------------

CHAIN

Material	galvanized steel
----------	------------------

VARIANTS

ref. no.

TM9-N

TM9-N

Lightweight aluminum safety tripod

ADDITIONAL PHOTOS

