




EN ISO 20345:2011 


ENDURANCE
ARKO BOA®
81184-03L

S3 SRC

Size: 36-48
Weight: 680 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Multipurpose



FEATURES

UPPER
Grain leather Hydro 1,8-2,0 mm
No ladder H.T. Fabric
Reflex insert

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO


INSOLE
Climaction-Fit 337

TOE CAP
CTC- Composite Toe Cap

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail - X
Method

TYPE
Low Shoe

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.52
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.23
	HEEL (CONTACT ANGLE °) ≥0.13	

SOLE 81
PU - PU

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

RESISTANT TO 3.0 mm. NAILS

CTC
Composite Toe Cap

Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Not detected by metal detector. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Flexible and comfortable



Lateral stability
dynamicHC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

BOA
ADJUSTABLE FIT

FIT TO GO FURTHER™

A patented closing system, which allows quick closing and opening. A multi coated stainless steel cable guarantees a personalized and effective fitting, obtaining a comfortable and practical closure

