



4 USERS



Supplied in a backpack



PRODUCT SPECIFICATIONS

CE EN795:2012 Tipo C
EN362 (connectors)**PACKAGING** 1 ud**MATERIAL** Polyester webbing.
Steel components.

COMPONENTS

X2 Steel screw-lock carabiners		30 kN
X4 Steel rings		22 kN
1 Steel ratchet		50 kN
1 Equipment carrying bag		-

FEATURES

- + Category III PPE.
- + Temporary horizontal lifeline type C, suitable for work requiring frequent horizontal movement.
- + With energy absorber and carabiners.
- + Suitable for lengths from 2 to 30 meters.
- + Capacity: 4 users.
- + Compatible with restraint systems, work positioning, fall arrest, rope access, and rescue.
- + Material: 50 mm wide polyester webbing.
- + Service Life: Estimated at 10 years from the date of manufacture, subject to mandatory annual inspections.

TECHNICAL DATA

Required minimum strength of anchor point	18 kN
Adjustable	SÍ
Webbing width	50 mm
Webbing strength	40 kN



SAFETOP.NET



+34 981 64 98 11



pedidos@safetop.net

SAFETOP[®]Rúa O Morrazo, 2 - 15171 - Iñás
(Oleiros, A Coruña) SPAIN