

## SUITABLE FOR VERTICAL AND HORIZONTAL USE



### Anchor

To attach a carabiner (not included)

### Retracting mechanism

To anchor a carabiner (not included)

### Steel cable

### Absorber

Energy 5.5-5.8kn

### Rotating carabiner

To anchor the harness

AVAILABLE SIZES	
<b>80806</b>	6m
<b>80810</b>	10m
<b>80815</b>	15m
<b>80820</b>	20m
<b>80825</b>	25m
<b>80335</b>	35m

### TECHNICAL SPECIFICATIONS

<b>Maximum Working Length</b>	Available IN 6, 10, 15, 20, 25, 35
<b>Cable Diameter</b>	4,8mm
<b>Static Strength</b>	12 kn during 3 min
<b>Maximum Working Load</b>	120 kg
<b>Weight</b>	6 m (6,5 Kg) / 10 m (7 kg) / 15 m (8,2 Kg) / 20 m (11 Kg) / 35 m (14 Kg)
<b>Packaging Unit</b>	1 ud
<b>Dimensions</b>	6-10 m: aprox 252x776x121 mm 15 m: aprox 284x790x118 mm 20 m: aprox 328x894x141 mm 35 m: aprox 330x960x145 mm
<b>Static Strength</b>	15 kn (cuerda/cinta) o 12kn (cable)
<b>TECHNICAL SPECIFICATIONS FOR ROTATING CARABINER</b>	
<b>Material</b>	Steel
<b>Type</b>	EN362 Clase T
<b>Opening</b>	21mm
<b>Strength</b>	23 kn
<b>Weight</b>	0,5kg

## PRODUCT SPECIFICATION



### EN 360: 2002 HORIZONTAL USE (PPE-R 1 1.060)

#### MATERIAL

Nylon housing, galvanized steel cable, and steel carabiner

#### APPLICATIONS

Vertical and horizontal work for construction, hydrocarbon production, maintenance, telecommunications, and confined spaces where worker mobility and fall protection are necessary.

#### LIFETIME



**Inspections:** The equipment must be inspected every 12 months by an authorized person or the manufacturer. Inspections should be recorded on the inspection sheet attached to the PPE, along with the instruction manual.

## FEATURES

- + Category II PPE (Personal Protective Equipment)
- + Retractable lifeline with a steel cable
- + Available in lengths of 6, 10, 15, 20, 25, and 35
- + Suitable for both vertical and horizontal use
- + 4.8mm galvanized steel cable with a loop finish, connected to a rotating lower carabiner
- + Integrated energy absorber made of polyester: 45mm wide.
- + The housing is made of high-strength nylon
- + The lower carabiner for harness attachment has a rotating head ("swivel ring") to prevent the cable from twisting if the operator turns
- + Fall indicator
- + Certified for a maximum load of 120 kg
- + Includes a handle for easy transport



**SAFETOP.NET**



+34 981 64 98 11



pedidos@safetop.net

**SAFETOP®**

Rúa O Morrazo, 2 - 15171 - Iñáis  
(Oleiros, A Coruña) SPAIN