

RUP 503-U

Lifting and lowering evacuation device

EN 1496/B



The RUP503-U lifting and lowering evacuation device is a rescue equipment component. Using the device, an injured person can be raised from a lower level to a higher level or lowered from a higher level to a lower level. The descent distance must not exceed 2 meters.

SPECIAL FEATURES



Protection for maximum user's weight of 200 kg



Suitable for explosion-hazard zones

PARAMETERS

WLL working load limit	200 kg
minimum breaking strength	21 kN
Safety Factor	10:1

KIT INCLUDES

Spring absorber	SDW
Długość korby - Wariant 1	300 mm
Siła wymagana do wyciągania ładunku w wariantie 1	10 kg
Przełożenie mechanizmu przekładni	7,2:1

CONSTRUCTION

Material	steel
Finishing	galvanization

COVER

Material	steel
Manufacture	powder coating
Color	orange

ROPE

Material	steel
Finishing	galvanization
Rope diameters $\varnothing$	6,3 mm

PROTEKT

PROTEKT Grzegorz Laszkiewicz Spolka z o.o. Starorudzka 9, 93-403 Lodz, POLAND
KRS: 0001009727 | REGON: 524047958 | NIP: 7292747932

WWW.PROTEKT.PL

EXPORT SALES DEPARTMENT Skromna 6, 93-405 Lodz, POLAND
Phone: +48 42 29 29 500, export@protekt.com.pl, Fax +48 42 680-20-93