

SUITABLE FOR VERTICAL AND HORIZONTAL USE



ANCHORAGE

to attach a carabiner (not included)

rollerMECHANISM

to attach a carabiner (not included)


SteelCABLE

ABSORBER

energy 5.5-5.8kn

CARABINER rotating

to anchor the harness



Horizontal use and fall protection on a type A edge, a steel edge thickness > 0.5 mm and without burrs (PPE-R/11.60)

AVAILABLE MEASURES

80806	6m
80810	10m
80815	15 metres
80820	20 metres
80825	25m
80830	30 metres
80835	35 metres

TECHNICAL DATA

Maximum working length	Available in 6, 10, 15, 20, 25, 35
Cable diameter	4.8 mm
Static resistance	12 knots for 3 minutes
Maximum workload	120 kg
Weight	6 m (6.5 kg) / 10 m (7 kg) / 15 m (8.2 kg) / 20 m (11 kg) / 35 m (14 kg)
Packaging unit	1 unit
Dimensions	6-10 m: approx. 252 x 776 x 121 mm 15 m: approx. 284 x 790 x 118 mm 20 m: approx. 328 x 894 x 141 mm 35 m: approx. 330 x 960 x 145 mm
Static resistance	15 kN (rope/tape) or 12 kN (cable)

TECHNICAL DATA SWIVEL CARABINER

Material	Steel
Type	EN362 Class T
Opening	21 millimetres
Resistance	23 knots
Weight	0.5kg

PRODUCT SPECIFICATIONS



EN 360: 2002
HORIZONTAL USE (PPE-R 1 1,060)

MATERIAL

Nylon casing, galvanised steel cable and steel carabiner

APPLICATIONS

Vertical and horizontal work for construction, hydrocarbon production, maintenance, telecommunications, and confined spaces where worker mobility and fall protection are necessary.

LIFETIME



Inspections: the equipment must be inspected every 12 months by an authorised person or by the manufacturer. Inspections must be recorded on the inspection form attached to the PPE together with the instruction manual.

FEATURES

- + Category III PPE
- + Retractable steel cable lifeline
- Available in 6, 10, 15, 20, 25, 30 and 35 metres.
- + Suitable for vertical and horizontal use
- + 4.8 mm galvanised steel cable with loop finish and connected to a swivel carabiner at the bottom
- + Fastening via a carabiner at the top (not included): oval steel fastening
- + Integrated polyester energy absorber: width 45 mm
- + Its casing is made of high-strength nylon.
- + The lower carabiner for attaching to the harness has a rotating head ("swivel ring"), which prevents the cable from twisting if the operator turns.
- + Fall indicator
- + Certified for a maximum load of 120 kg
- + Includes handle for easy transport



SAFETOP.NET



+34 981 64 98 11



pedidos@safetop.net

SAFETOP®

Rúa O Morrazo, 2 - 15171 - Iñás
(Oleiros, A Coruña) SPAIN