



EN ISO 20345:2011



ENDURANCE

BADIA

81088-06L

S3 SRC
Size: 36-48

Weight: 640 gr.

Fit: 11

Working Environment:

Building, Wood-metal carpentry, Farming and Gardening, Multipurpose


FEATURES
UPPER

 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Full Grain leather Hydro

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Flyfit

TOE CAP


CTC- Composite Toe Cap

RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

TYPE

Low Shoe


SRC (SRA+SRB)

SOLE 81		
SRA CERAMIC DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE 7°) ≥0.28	0.52 0.48
SRB STEEL GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE 7°) ≥0.13	0.23 0.18

EN ISO 20345:2011

TECHNOLOGIES
Removable Insole


The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.


Protection elements


Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.


Lateral stability


Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.


Torsional stability


Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


Electrical features


Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.


Other


Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.