



EN ISO 20345:2011 

ATLANTIDA
ELDORADO
80117-08L

S3 HRO HI WR SRC

Size: 38-48
Weight: 765 gr.

Fit: 11


Working Environment:
Building, Wood-metal carpentry,
Engineering, Farming and
Gardening



FEATURES

- UPPER**
Full Grain-Anilina Leather-Hydro
1,8-2,0 mm
Reflex insert
- LINING**
3D Air circulation 320 gr.
- ANTISLIP LINING**
DUALMICRO
- INSOLE**
Blow-fit 2.0
- TOE CAP**
CTC- Composite Toe Cap
- RESISTANCE TO PERFORATION**
Zero(K) Perforation resistant
- TYPE**
Ankle boot
- SOLE**
PU-RUBBER VIBRAM-HRO-SRC
Sole with anti-wear scaff cap.
Outsole in VIBRAM rubber,
resistant to 300° C by contact
(HRO), to acids and oils. Design
with self-cleaning outsole, with
SRC Antislip standard.

TECHNOLOGIES


- Removable Insole**
blow fit 2.0
Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The E.V.A. HD perforad and thermoformed support ensures comfort and energy absorption
- Protection elements**
ZERO(k)
ANTIPERFORATION 
Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



- Lateral stability**
dynamic HC control technology
Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.
- Torsional stability**
STABIL•ACTIVE
Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



- Electrical features**
WED
Wire Electricity Discharge
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.
- Other**
DUALMICRO DUALWICKBO
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)

SOLE 80
PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.43
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19
		0.13

EN ISO 20344:2011