



EN ISO 20345:2011



HORIZON
ILLINOIS
52023-15L

S3 SRC

Size: 36-48
Weight: 700 gr.

Fit: 10,5

Working Environment:
Multipurpose, Building, Logistics and Light Industry, Farming and Gardening



FEATURES

UPPER
Grain leather Hydro Fabric of High Tenacity

LINING
3D Air circulation 320 gr.

INSOLE
Climaction-Fit 337

TOE CAP
Steel Toe Cap

RESISTANCE TO PERFORATION
Steel Plate

TYPE
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
STEEL PROTECTION

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.



SRC (SRA+SRB)

SOLE 52 - 53 PU - PU		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.36 0.42
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.14

EN ISO 20344:2011


Lateral stability
dynamic HC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUAL MICRO DWT WICBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.