



EN ISO 20345:2011



ATLANTIDA

WELD
80143-00L
S3 HRO HI SRC
Size: 38-48

Weight: 785 gr.

Fit: 11

Working Environment:

 Building, Wood-metal carpentry,
 Engineering, Farming and
 Gardening


FEATURES

UPPER

 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Soft Full Grain Leather Hydro

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Flyfit

TOE CAP

CTC- Composite Toe Cap

RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM-HRO-SRC

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM rubber,
 resistant to 300° C by contact
 (HRO), to acids and oils. Design
 with self-cleaning outsole, with
 SRC Antislip standard.

TECHNOLOGIES

Removable Insole


FLYFIT

 The upper layer in contact with the
 foot is made of a highly resistant
 netting to ensure exceptional
 absorption of dampness. A self-
 forming antibacterial foam layer
 ensures comfort and correct support
 of the foot.


Protection elements

ZERO(k)

ANTIPERFORATION



Composite Toe Cap

 Toecap made of plastic, incredibly
 light and resistant to impact of over
 200J, elastic. Athermic. Not detected
 by metal detector. Fabric anti-
 perforation foil. Resistant to over
 1100 N with zero perforation.


Lateral stability

dynamic HC control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability


STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features

WED

Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

DUALMICRO
DUALMICRO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 80
 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.43
	HEEL (CONTACT ANGLE 1°) ≥0.28	0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE 1°) ≥0.13	0.13

EN ISO 20344:2011