



EN ISO 20345:2011



SKIPPER
AUCKLAND
94378-00L

S3 SRC

Size: 38-48
Weight: 560 gr.

Fit: 11

Working Environment:
Logistics and Light Industry,
Components and Automotive, ESD
Areas



FEATURES

UPPER

Digitex Hydro Airy
MicroFiber Suede with Pro-tech
SXT light 1,6-1,8 mm

LINING

Breezy 3D, two-layers
combination

ANTISLIP LINING DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail - X
Method

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements



Toecap "Alu Sxt 2.0" with
differentiated thicknesses, resistant
to 200J. Non metal perforation
resistant Insert to over 1100 N with a
3.0 mm truncated cone nail. Protection
over the entire sole of the foot.
Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other



Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.



SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.41
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.26
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011