



ATEX, CE, EAC Ex e IECEx

Approved IP66 / IP67. UL approved for Class I Div 1. For harsh environments and extreme temperatures



PRODUCT SPECIFICATIONS

Fixed-lifespan 4-gas detector (2 years)

User Options	Configure alarm settings: Low, High, TWA, STEL
	Alarm lockout
	Configure calibration and bump test reminders
	Worker assignment and location
	Always on

Configurable

Built-in Bluetooth

Low-power infrared LEL sensor

SO₂ sensor as a configurable option

Configurable alarms (audible mode / silent mode)

Compatible with Device Configurator (DC)

FEATURES

- + Portable detector designed to prevent risks from the most common hazardous gases in workplace environments: Combustible Gases (LEL), Oxygen (O₂), Hydrogen Sulfide (H₂S), Carbon Monoxide (CO), Sulfur Dioxide (SO₂)
- + Display with simple icons showing gas levels and device status
- + On-screen icon reading; in the event of a gas alarm, the screen icon will light up so workers can quickly evacuate the area
- + Bluetooth configuration with an app to view concentrations and data, all organized into a report ready to send
- + 2-month battery life with a 4.5-hour charge, and up to 4 months if the detector is turned off at the end of each shift
- + Fixed 2-year lifespan
- + Small, lightweight, and easy to carry
- + New Series 1 sensors respond in seconds, even under very demanding temperatures
- + Intuitive and easy to use: single-button operation
- + No need to replace sensors
- + Replaceable rechargeable battery
- + Vehicle charger